



- 1 Flexible high quality elastomeric insert**  
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Multi directional movement**
- 3 Quick and easy installation**  
Solid, but light aluminium brackets for quick installation in screed or tiled floorings
- 4 MultiHole mounting bracket**  
for secure fixing

**Flexible adaptation to site conditions**  
Available with adjustable installation height

Expansion joint cover	Joint width	Total movement	Visible width	Joint width total	Joint height	Load bearing capacity	Load bearing capacity*
	$b_f \text{ max}$ [mm]						
FV 35/15	30	10 ( $\pm 5$ )	35	108	15	30	30
FV 35/20	30	10 ( $\pm 5$ )	35	108	20	30	30
FV 35/25	30	10 ( $\pm 5$ )	35	108	25	30	30
FV 35/35	30	10 ( $\pm 5$ )	35	125	35	30	30
FV 35/50	30	10 ( $\pm 5$ )	35	125	50	30	30
FV 35/4055	30	10 ( $\pm 5$ )	35	108	40, 45, 50, 55	30	30
FV 35/6075	30	10 ( $\pm 5$ )	35	108	60, 65, 70, 75	30	30
FV 35/7590	30	10 ( $\pm 5$ )	35	108	75, 80, 85, 90	30	30
FV 35/90105	30	10 ( $\pm 5$ )	35	108	90, 95, 100, 105	30	30

No continuous use

All info on load capacities apply to doweled, not to floating installation.

For installation in asphalt, please ask for our technical advice.

**Production length:** 4 m

**Standard colors:** black, grey, beige, brown

