

FS 160

FOR HEAVY DUTY FLOORS

MIGUTRANS

HEAVY-DUTY ALL-METAL JOINT SOLUTIONS FOR LARGE TRAFFIC LOADS



- 1 Solid all-metal expansion joint**
hard wearing, maintenance-free, long lasting
- 2 Visible surface has no gaps**
avoids dirt accumulation
- 3 Striated surface**
ensures good skid resistance
- 4 Articulated telescoping system**
absorbs movement in 3 directions
- 5 MultiHole mounting bracket**
for secure fixing

Now available Anodized!

This expansion joint cover is on offer in anodized colours as of now. Available as standard in the four colours shown below, we will be pleased to offer you further colours upon request

Expansion joint cover	Joint width max.	Total movement	Visible width	Joint width total	Joint height	Load bearing capacity	Load bearing capacity	Load bearing capacity
	b_f [mm]							
FS 160/22*	130	60 (± 30)	162	280	22	300	70	6,5
FS 160/30*	130	60 (± 30)	162	280	30	300	70	6,5
FS 160/42	130	60 (± 30)	162	284	42	300	70	6,5
FS 160/52	130	60 (± 30)	162	284	52	300	70	6,5
FS 160/62	130	60 (± 30)	162	284	62	300	70	6,5
FS 160/77	130	60 (± 30)	162	284	77	300	70	6,5
FS 160/87	130	60 (± 30)	162	284	87	300	70	6,5
FS 160/97	130	60 (± 30)	162	284	97	300	70	6,5

* Minimum joint width 130 mm

Production length: 4 m

Standard colour: Aluminium

Further installation heights on request.

