

FSV 235

FOR HEAVY DUTY FLOORS

MIGUTRANS

HEAVY-DUTY ALL-METAL JOINT SOLUTIONS FOR LARGE TRAFFIC LOADS




- 1 Visible surface has no gaps**
avoids dirt accumulation
- 2 Removable bridging unit**
serviceable for inspection, replaceable centre parts
- 3 Striated surface**
ensures good skid resistance
- 4 Articulated telescoping system**
absorbs movement in 3 directions
- 5 Solid all-metal expansion joint**
hard wearing, maintenance-free, long lasting

Expansion joint cover	Joint width max. b_f [mm]	Total movement Δb_f [mm]	Visible width b_s [mm]	Joint width total b_t [mm]	Joint height h [mm]	Load bearing capacity [kN]	Load bearing capacity [kN]	Load bearing capacity solid plastic tyres [kg/mm]
FSV 235/45	150	60 (± 30)	235	357	45	300	70	6,5
FSV 235/80	150	60 (± 30)	235	357	80	300	70	6,5
FSV 235/130	150	60 (± 30)	235	357	130	300	70	6,5

Production length: 3 m

Standard colour: Aluminium

Alternative heights on request.



www.migua.com | info@migua.com
06/2019 – Subject to technical changes without notice