

FS 110 ES

FOR FLOOR SURFACES WITH HIGH DEMANDS ON DESIGN AND APPEARANCE

MIGUTRANS

HEAVY-DUTY ALL-METAL JOINT SOLUTIONS FOR LARGE TRAFFIC LOADS



- 1 **Stainless Steel, brass or 3M tape surface**
for highest demands and skid resistance (R9 - R13)
- 2 **Visible surface has no gaps**
avoids dirt accumulation
- 3 **Articulated telescoping system**
absorbs movement in 3 directions
- 4 **Solid all-metal expansion joint**
hard wearing, maintenance free, long lasting
- 5 **Optically attractive, high quality surface**

Expansion joint cover	Joint width max.	Total movement	Visible width	Joint width total		Joint height	Load bearing capacity	Load bearing capacity
	b_f [mm]			Δb_f [mm]	b_t [mm]			
FS 110/22 ES*	75	30 (±15)	113	226	23	300	70	
FS 110/30 ES	75	30 (±15)	113	226	31	300	70	
FS 110/42 ES	75	30 (±15)	113	230	43	300	70	
FS 110/52 ES	75	30 (±15)	113	230	53	300	70	
FS 110/62 ES	75	30 (±15)	113	230	63	300	70	
FS 110/77 ES	75	30 (±15)	113	230	78	300	70	
FS 110/87 ES	75	30 (±15)	113	230	88	300	70	
FS 110/97 ES	75	30 (±15)	113	230	98	300	70	

* Minimum joint width 75 mm.

Production length: 4 m, metal inserts: 2 x 2 m

Standard colour: aluminum, inserts: stainless steel, brass or black

Larger installation heights on request. Also available with different inserts.

